



Covert Antenna Systems



Dual Band Fender Mount Antennas Combinations of VHF with Either UHF, 700 or 800MHz

- Looks exactly like the original antenna
- Specific to the make, model, and year of the vehicle
- Install one covert antenna instead of two
- Won't interfere with AM/FM radio

MODEL NUMBERS	DB-VHF/UHF	DB-VHF/700	DB-VHF/CEL
FREQUENCY RANGE (MHz)	150-174 / 406-512	150-174 / 760-870	150-174 / 806-866
BANDWIDTH (MHz)	24 / 34*	10* / 110	10* / 60
POWER RATING (watts)	VHF:150 / UHF:150	VHF:150 / 700:35	VHF:150 / CEL:35
ISOLATION (dB)	35	35	35
FINISH	OEM match		
MAXIMUM HEIGHT (inches)	31	32	32
MOUNTING HARDWARE	OEM hardware		
MAST MATERIAL	Fiberglass	Stainless steel	Stainless steel
FEED LINES (17' per radio)	RG58		
CONNECTOR (one per radio)	PL259, Mini-UHF, BNC, TNC, SMA, N		

WHEN ORDERING: Please provide the Year, Make, Model and Trim Line of your vehicle.

* Specify operating frequency



Certified ISO 9001:2008
Certified DBE/WBE
© 2011 STI-CO Industries, Inc.

